

Injecting parameters in content views

Description

It is possible to dynamically inject variables in content view templates by listening to the `ezpublish.pre_content_view` event.

The event listener method receives an `eZ\Publish\Core\MVC\Symfony\Event\PreContentViewEvent` object

Example

The following example will inject `foo` and `osTypes` variables in all content view templates.

```
<?php

namespace Acme\DemoBundle\EventListener;
use
eZ\Publish\Core\MVC\Symfony\Event\PreContentViewEvent;

class PreContentViewListener
{
    public function onPreContentView(
        PreContentViewEvent $event )
    {
        // Get content view object and inject whatever
        // You may add some custom business logic here.
        $contentView = $event->getContentView();
        $contentView->addParameters(
            array(
                'foo'           => 'bar',
                'osTypes'       => array( 'osx',
                'linux', 'win' )
            )
        );
    }
}
```

Service configuration

```
parameters:
    ezdemo.pre_content_view_listener.class:
        Acme\DemoBundle\EventListener\PreContentViewListener

services:
    ezdemo.pre_content_view_listener:
        class: %ezdemo.pre_content_view_listener.class%
        tags:
            - {name: kernel.event_listener, event:
                ezpublish.pre_content_view, method: onPreContentView}
```

In this topic:

- [Description](#)
- [Example](#)

Related topics:

- [Content Rendering](#)
- [Default view templates](#)

