

# ez\_trans\_prop

- Description
- Prototype and Arguments
  - Main language use
- Usage

>= 5.4 / 2014.09

## Description

`ez_trans_prop()` is a generic, low level Twig helper which correct translated value of a multi valued(translations) property.

If the current language cannot be found as a translation for content, main language (see [further down for details](#)) will be used if this is supported by provided **object**. This behavior is identical when forcing a language using **forcedLanguage**.

## Prototype and Arguments

`ez_trans_prop( ValueObject object, string property[, string forcedLanguage] )`

Argument name	Type	Description
object	eZ\Publish\Core\Repository\Values\ValueObject	ValueObject object <b>property</b> belongs to.
property	string	Property to get translated value from, logic is using one of the following (in this order): <ul style="list-style-type: none"><li>▪ <i>property</i> "{<b>property</b>}s"</li><li>▪ <i>method</i> "get{<b>property</b>}"</li></ul>
forcedLanguage	string	Language we want to force (e.g. "eng-US"), otherwise takes prioritized languages from SiteAccess settings.

## Main language use

Main language is attempted to be applied in the following way for Value objects that support this:

- *property*: Use **mainLanguageCode** property if it exists, but not if **alwaysAvailable** exists and is true
- *method*: Provide `$language = null` as only argument to method, depends on logic of ValueObject if this gives a fallback value or not

## Usage

Example below shows how this function can be used to get the Content name with exact same result as using `ez_content_name(content)`

```
<span>{{ ez_trans_prop( versionInfo, "name" ) }}</span>
```