REST API Authentication

The REST API supports two authentication methods: session, and basic.

- Session-based authentication is meant to be used for AJAX operations. It will let you
 re-use the visitor's session to execute operations with their permissions.
- Basic authentication is often used when writing cross-server procedures, when one remote application executes operations on one/several eZ Platform instances (remote publishing, maintenance, etc).

Session-based is the default authentication method, as this is needed for UI.

Session based authentication

This authentication method requires a Session cookie to be sent with each request.

If this authentication method is used with a web browser, this session cookie is automatically available as soon as your visitor logs in. Add it as a cookie to your REST requests, and the user will be authenticated.

Logging in

It is also possible to create a session for the visitor if they aren't logged in yet. This is done by sending a **POST** request to /user/sessions. Logging out is done using a **DELETE** request on the same resource.

More information

Session-based authentication chapter of the REST specifications

HTTP Basic authentication

To enable HTTP Basic authentication, you need to edit app/config/security.yml, and add/uncomment the following block. Note that this is enabled by default.

```
ezpublish_rest:

pattern: ^/api/ezp/v2
stateless: true
ezpublish_http_basic:
realm: eZ Publish REST API
```

Basic authentication requires the username and password to be sent *(username:password)*, based 64 encoded, with each request, as explained in RFC 2617.

Most HTTP client libraries as well as REST libraries do support this method one way or another.

Raw HTTP request with basic authentication

GET / HTTP/1.1
Host: api.example.com

Accept: application/vnd.ez.api.Root+json

Authorization: Basic QWxhZGRpbjpvcGVuIHNlc2FtZQ==

In this topic:

- Session based authentication
 - Logging in
- HTTP Basic authentication