

Signals reference

This page references **all available signals**, triggered by ("Public") Repository API in "Platform Stack", which you can listen to.

For more information, check [SignalSlot documentation](#) and the [cookbook recipe on how to listen to signals](#).

Signals are ordered by Repository service:

- [ContentService](#)
- [ContentTypeService](#)
- [LanguageService](#)
- [LocationService](#)
- [ObjectStateService](#)
- [RoleService](#)
- [SectionService](#)
- [TrashService](#)
- [URLAliasService](#)
- [URLWildcardService](#)
- [UserService](#)

All signals are relative to `eZ\Publish\Core\SignalSlot\Signal` namespace.

Transactions

As of eZ Publish Platform 5.3.3 and higher signals are sent after transactions are executed making signals transaction safe.

ContentService

Signal type	Properties	Triggered by	When
<code>ContentService\AddRelationSignal</code>	<ul style="list-style-type: none">• <code>srcContentId</code> (source contentId, aka referrer)• <code>srcVersionNo</code>• <code>dstContentId</code> (destination contentId, aka target)	<code>ContentService::addRelation()</code>	After
<code>ContentService\AddTranslationInfoSignal</code>	N/A	<code>ContentService::addTranslationInfo()</code>	After
<code>ContentService\CopyContentSignal</code>	<ul style="list-style-type: none">• <code>srcContentId</code> (original content ID)• <code>srcVersionNo</code>• <code>dstContentId</code> (contentId of the copy)• <code>dstVersionNo</code>• <code>dstParentLocationId</code> (locationId where the content has been copied)	<code>ContentService::copyContent()</code>	After
<code>ContentService\CreateContentDraftSignal</code>	<ul style="list-style-type: none">• <code>contentId</code>• <code>versionNo</code>• <code>userId</code> (Id of user used to create the draft, or null - current user)	<code>ContentService::createContentDraft()</code>	After
<code>ContentService\CreateContentSignal</code>	<ul style="list-style-type: none">• <code>contentId</code>• <code>versionNo</code>	<code>ContentService::createContent()</code>	After
<code>ContentService\DeleteContentSignal</code>	<ul style="list-style-type: none">• <code>contentId</code>	<code>ContentService::deleteContent()</code>	After
<code>ContentService\DeleteRelationSignal</code>	<ul style="list-style-type: none">• <code>srcContentId</code>• <code>srcVersionNo</code>• <code>dstContentId</code>	<code>ContentService::deleteRelation()</code>	After
<code>ContentService\DeleteVersionSignal</code>	<ul style="list-style-type: none">• <code>contentId</code>• <code>versionNo</code>	<code>ContentService::deleteVersion()</code>	After

ContentService\PublishVersionSignal	<ul style="list-style-type: none"> • contentId • versionNo 	ContentService::publishVersion()	After
ContentService\TranslateVersionSignal	<ul style="list-style-type: none"> • contentId • versionNo • userId 	ContentService::translationVersion()	After
ContentService\UpdateContentMetadataSignal	<ul style="list-style-type: none"> • contentId 	ContentService::updateContentMetadata()	After
ContentService\UpdateContentSignal	<ul style="list-style-type: none"> • contentId • versionNo 	ContentService::updateContent()	After

ContentTypeService

Signal type	Properties	Triggered by
ContentTypeService\AddFieldDefinitionSignal	<ul style="list-style-type: none"> • contentTypeDraftId 	ContentTypeService::addFieldDefinition()
ContentTypeService\AssignContentTypeGroupSignal	<ul style="list-style-type: none"> • contentTypeId • contentTypeGroupId 	ContentTypeService::assignContentTypeGroup()
ContentTypeService\CopyContentTypeSignal	<ul style="list-style-type: none"> • contentTypeId • userId 	ContentTypeService::copyContentType()
ContentTypeService\CreateContentTypeDraftSignal	<ul style="list-style-type: none"> • contentTypeId 	ContentTypeService::createContentTypeDraft()
ContentTypeService\CreateContentTypeGroupSignal	<ul style="list-style-type: none"> • groupId 	ContentTypeService::createContentTypeGroup()
ContentTypeService\CreateContentTypeSignal	<ul style="list-style-type: none"> • contentTypeId 	ContentTypeService::createContentType()
ContentTypeService\DeleteContentTypeGroupSignal	<ul style="list-style-type: none"> • contentTypeGroupId 	ContentTypeService::deleteContentTypeGroup()
ContentTypeService\DeleteContentTypeSignal	<ul style="list-style-type: none"> • contentTypeId 	ContentTypeService::deleteContentType()
ContentTypeService\PublishContentTypeDraftSignal	<ul style="list-style-type: none"> • contentTypeDraftId 	ContentTypeService::publishContentTypeDraft()
ContentTypeService\RemoveFieldDefinitionSignal	<ul style="list-style-type: none"> • contentTypeDraftId • fieldDefinitionId 	ContentTypeService::removeFieldDefinition()
ContentTypeService\UnassignContentTypeGroupSignal	<ul style="list-style-type: none"> • contentTypeId • contentTypeGroupId 	ContentTypeService::unassignContentTypeGroup()
ContentTypeService\UpdateContentTypeDraftSignal	<ul style="list-style-type: none"> • contentTypeDraftId 	ContentTypeService::updateContentTypeDraft()
ContentTypeService\UpdateContentTypeGroupSignal	<ul style="list-style-type: none"> • contentTypeGroupId 	ContentTypeService::updateContentTypeGroup()
ContentTypeService\UpdateFieldDefinitionSignal	<ul style="list-style-type: none"> • contentTypeDraftId • fieldDefinitionId 	ContentTypeService::updateFieldDefinition()

LanguageService

Signal type	Properties	Triggered by	When
LanguageService\CreateLanguageSignal	<ul style="list-style-type: none"> • languageId 	LanguageService::createLanguage()	After
LanguageService\DeleteLanguageSignal	<ul style="list-style-type: none"> • languageId 	LanguageService::deleteLanguage()	After
LanguageService\DisableLanguageSignal	<ul style="list-style-type: none"> • languageId 	LanguageService::disableLanguage()	After
LanguageService\EnableLanguageSignal	<ul style="list-style-type: none"> • languageId 	LanguageService::enableLanguage()	After
LanguageService\UpdateLanguageNameSignal	<ul style="list-style-type: none"> • languageId • newName 	LanguageService::updateLanguageName()	After

LocationService

Signal type	Properties	Triggered by	When
LocationService\CopySubtreeSignal	<ul style="list-style-type: none"> • subtreeId (top locationId of the subtree to be copied) • targetParentLocationId 	LocationService::copySubtree()	After

LocationService\CreateLocationSignal	<ul style="list-style-type: none"> • contentId • locationId 	LocationService::createLocation()	After
LocationService\DeleteLocationSignal	<ul style="list-style-type: none"> • contentId • locationId 	LocationService::deleteLocation()	After
LocationService\HideLocationSignal	<ul style="list-style-type: none"> • contentId • locationId 	LocationService::hideLocation()	After
LocationService\UnhideLocationSignal	<ul style="list-style-type: none"> • contentId • locationId 	LocationService::unhideLocation()	After
LocationService\MoveSubtreeSignal	<ul style="list-style-type: none"> • subtreeId • newParentLocationId 	LocationService::moveSubtree()	After
LocationService\SwapLocationSignal	<ul style="list-style-type: none"> • content1Id • location1Id • content2Id • location2Id 	LocationService::swapLocation()	After
LocationService\UpdateLocationSignal	<ul style="list-style-type: none"> • contentId • locationId 	LocationService::updateLocation()	After

ObjectStateService

Signal type	Properties	Triggered by
ObjectStateService\CreateObjectStateGroupSignal	<ul style="list-style-type: none"> • objectStateGroupId 	ObjectStateService::createObjectStateGroup()
ObjectStateService\CreateObjectStateSignal	<ul style="list-style-type: none"> • objectStateGroupId • objectStateId 	ObjectStateService::createObjectState()
ObjectStateService\DeleteObjectStateGroupSignal	<ul style="list-style-type: none"> • objectStateGroupId 	ObjectStateService::deleteObjectStateGroup()
ObjectStateService\DeleteObjectStateSignal	<ul style="list-style-type: none"> • objectStateId 	ObjectStateService::deleteObjectState()
ObjectStateService\SetContentStateSignal	<ul style="list-style-type: none"> • contentId • objectStateGroupId • objectStateId 	ObjectStateService::setContentState()
ObjectStateService\SetPriorityOfObjectStateSignal	<ul style="list-style-type: none"> • objectStateId • priority 	ObjectStateService::setPriorityOfObjectState()
ObjectStateService\UpdateObjectStateGroupSignal	<ul style="list-style-type: none"> • objectStateGroupId 	ObjectStateService::updateObjectStateGroup()
ObjectStateService\UpdateObjectStateSignal	<ul style="list-style-type: none"> • objectStateId 	ObjectStateService::updateObjectState()

RoleService

Signal type	Properties	Triggered by	When
RoleService\AddPolicySignal	<ul style="list-style-type: none"> • roleId • policyId 	RoleService::addPolicy()	After
RoleService\AssignRoleToUserGroupSignal	<ul style="list-style-type: none"> • roleId • userGroupId • roleLimitation 	RoleService::assignRoleToUserGroup()	After
RoleService\AssignRoleToUserSignal	<ul style="list-style-type: none"> • roleId • userId • roleLimitation 	RoleService::assignRoleToUser()	After
RoleService\CreateRoleSignal	<ul style="list-style-type: none"> • roleId 	RoleService::createRole()	After
RoleService\DeleteRoleSignal	<ul style="list-style-type: none"> • roleId 	RoleService::deleteRole()	After
RoleService\RemovePolicySignal	<ul style="list-style-type: none"> • roleId • policyId 	RoleService::removePolicy()	After
RoleService\UnassignRoleFromUserGroupSignal	<ul style="list-style-type: none"> • roleId • userGroupId 	RoleService::unassignRoleFromUserGroup()	After
RoleService\UnassignRoleFromUserSignal	<ul style="list-style-type: none"> • roleId • userId 	RoleService::unassignRoleFromUser()	After

RoleService\UpdatePolicySignal	<ul style="list-style-type: none"> policyId 	RoleService::updatePolicy()	After
RoleService\UpdateRoleSignal	<ul style="list-style-type: none"> roleId 	RoleService::updateRole()	After

SectionService

Signal type	Properties	Triggered by	When
SectionService\AssignSectionSignal	<ul style="list-style-type: none"> contentId sectionId 	SectionService::assignSection()	After
SectionService\CreateSectionSignal	<ul style="list-style-type: none"> sectionId 	SectionService::createSection()	After
SectionService\DeleteSectionSignal	<ul style="list-style-type: none"> sectionId 	SectionService::deleteSection()	After
SectionService\UpdateSectionSignal	<ul style="list-style-type: none"> sectionId 	SectionService::updateSection()	After

TrashService

Signal type	Properties	Triggered by	When
TrashService\DeleteTrashItemSignal	<ul style="list-style-type: none"> trashItemId 	TrashService::deleteTrashItem()	After
TrashService\EmptyTrashSignal	N/A	TrashService::emptyTrash()	After
TrashService\RecoverSignal	<ul style="list-style-type: none"> trashItemId newParentLocationId newLocationId 	TrashService::recover()	After
TrashService\TrashSignal	<ul style="list-style-type: none"> locationId 	TrashService::trash()	After

URLAliasService

Signal type	Properties	Triggered by	When
URLAliasService\CreateGlobalUrlAliasSignal	<ul style="list-style-type: none"> urlAliasId 	URLAliasService::createGlobalUrlAlias()	After
URLAliasService\CreateUrlAliasSignal	<ul style="list-style-type: none"> urlAliasId 	URLAliasService::createUrlAlias()	After
URLAliasService\RemoveAliasesSignal	<ul style="list-style-type: none"> aliasList 	URLAliasService::removeAliases()	After

URLWildcardService

Signal type	Properties	Triggered by	When
URLWildcardService\CreateSignal	<ul style="list-style-type: none"> urlWildcardId 	URLWildcardService::create()	After
URLWildcardService\RemoveSignal	<ul style="list-style-type: none"> urlWildcardId 	URLWildcardService::remove()	After
URLWildcardService\TranslateSignal	<ul style="list-style-type: none"> url 	URLWildcardService::translate()	After

UserService

Signal type	Properties	Triggered by	When
UserService\AssignUserToUserGroupSignal	<ul style="list-style-type: none"> userId userGroupId 	UserService::assignUserToUserGroup()	After
UserService\CreateUserGroupSignal	<ul style="list-style-type: none"> userGroupId 	UserService::createUserGroup()	After
UserService\CreateUserSignal	<ul style="list-style-type: none"> userId 	UserService::createUser()	After
UserService\DeleteUserGroupSignal	<ul style="list-style-type: none"> userGroupId 	UserService::deleteUserGroup()	After

UserService\DeleteUserSignal	<ul style="list-style-type: none">• userId	UserService::deleteUser()	After
UserService\MoveUserGroupSignal	<ul style="list-style-type: none">• userGroupId• newParentId	UserService::moveUserGroup()	After
UserService\UnAssignUserFromUserGroupSignal	<ul style="list-style-type: none">• userId• userGroupId	UserService::unAssignUserFromUserGroup()	After
UserService\UpdateUserGroupSignal	<ul style="list-style-type: none">• userGroupId	UserService::updateUserGroup()	After
UserService\UpdateUserSignal	<ul style="list-style-type: none">• userId	UserService::updateUser()	After